
















PRODUCT NAME	PRODUCT IMAGE	PRODUCT SPECS	PRICE
Covert Cameras & Equipment			
Air Cleaner 1 Wireless		<p>Camera Specifications:</p> <ul style="list-style-type: none"> • 92 degree field of view • 3.6mm Lens • 1/3 DSP Color CCD image Sensor, 1/4 DSP B/W • 380 lines of resolutions color, 420 lines B/W • 0.5 LUX color, .05 B/W • DC 12V power • NTSC • Audio is not available • Transmitter / Receiver Specifications: • 4-channel operations (camera) • 8 channel scroll capable (receiver) • 300 – 700 foot line of sight (LOS) approximate range • (LOS is dependent upon, obstructions and interference from other wireless devices) <p>Includes Extra Filters Black soft case Hidden Video camera systems Power supply RCA Cable Instructions Size 9 1/2" x 5 1/4" x 6"</p>	\$350.00
Back Pack		<p>Camera Specifications:</p> <ul style="list-style-type: none"> • 92 degree field of view • 3.6mm Lens • 1/3 DSP Color CCD image Sensor 1/4 DSP B/W • 380 lines of resolutions color, 420 lines B/W • 0.5 LUX Color, .05 B/W • DC 12V power • NTSC • Power supply • RCA Cable • Instructions 	\$375.00
3 Ring Binder Camera		<p>Camera Specifications:</p> <ul style="list-style-type: none"> • 92 degree field of view • 3.6mm Lens • 1/3 DSP Color CCD image Sensor 1/4 DSP B/W • 380 lines of resolutions color, 420 lines B/W • 0.5 LUX Color, .05 B/W • DC 12V power • NTSC • Power supply • RCA Cable • Instructions <p>Hardwire and Wireless Configurations Available</p>	\$280.00




PRODUCT NAME	PRODUCT IMAGE	PRODUCT SPECS	PRICE
Computer Speakers 1 Wireless		<p>Camera Specifications:</p> <ul style="list-style-type: none"> • 92 degree field of view • 3.6mm Lens • 1/3 DSP Color CCD image Sensor ¼ DSP B/W • 380 lines of resolutions color, 420 lines B/W • 0.5 LUX color .05 B/W • DC 12V power • NTSC • Audio is not available <p>Transmitter / Receiver Specifications:</p> <ul style="list-style-type: none"> • 4-channel operations (camera) • 8 channel scroll capable (receiver) • 300 – 700 foot line of sight (LOS) approximate range • (LOS is dependent upon, obstructions and interference from other wireless devices) <p>Includes</p> <ul style="list-style-type: none"> • Hidden Video camera systems • Power supply • RCA Cable • Instructions • Size • 7 3/8" x 4" x 3" <p>Different Distance Configurations Available.</p>	\$295.00
Briefcase Camera and Recorder		<p>Custom Built</p> <p>Price and quality varies</p>	<p>Custom Built</p> <p>Price and quality varies</p>
Jean Jacket		<p>420 LOR B/W camera built into the front pocket button,</p> <p>This wireless systems will transmit vivid video up to 1000' and includes a highgain receiver and power supplies.</p> <p>Can be made Hardwired Can be made Color</p>	\$395.00
Emergency Lights Wireless		<p>Camera Specifications:</p> <ul style="list-style-type: none"> • 92 degree field of view • 3.6mm Lens • 1/3 DSP Color CCD image Sensor, ¼ DSP B/W • 380 lines of resolutions color, 420 lines B/W • 0.5 LUX Color, .05 B/W • DC 12V power • NTSC • Audio is not available 	\$385.00

PRODUCT NAME	PRODUCT IMAGE	PRODUCT SPECS	PRICE
		<p>Transmitter / Receiver Specifications: 4-channel operations (camera) 8 channel scroll capable (receiver) 300 – 700 foot line of sight (LOS) approximate range (LOS is dependent upon, obstructions and interference from other wireless devices)</p> <p>Includes Hidden Video camera systems Power supply RCA Cable Instructions</p> <p>Hardwire also available</p>	
Exit Sign Wireless		<p>Camera Specifications:</p> <ul style="list-style-type: none"> • 92 degree field of view • 3.6mm Lens • 1/3 DSP Color CCD image Sensor, 1/4 DSP B/W • 380 lines of resolutions color, 420 lines B/W • 0.5 LUX Color, .05 B/W • DC 12V power • NTSC • Audio is not available <p>Transmitter / Receiver Specifications: 4-channel operations (camera) 8 channel scroll capable (receiver) 300 – 700 foot line of sight (LOS) approximate range (LOS is dependent upon, obstructions and interference from other wireless devices)</p> <p>Includes Hidden Video camera systems Power supply RCA Cable Instructions Size 11 5/8" x 7 1/2" x 2"</p>	\$385.00
Exit Sign Hardwired		<p>Camera Specifications:</p> <ul style="list-style-type: none"> • Working, fully functional exit sign • Clear overhead view of individual faces passing underneath • Ideal for uncovering and documenting fraud and theft inside an office • Lighted sign and surveillance equipment both powered by 12v DC. Wired power ensures continuous operation of both sign and camera equipment • Red LED array illuminates sign ensuring years of trouble service. Never replace sign bulbs again 	Black & White Camera \$250.00 Day/Night Camera \$395.00




PRODUCT NAME	PRODUCT IMAGE	PRODUCT SPECS	PRICE
Alarm Clock Camera1 - Wireless		<p>Camera Specifications:</p> <ul style="list-style-type: none"> Fully functional AM/FM clock radio B/W, 420 TVL, .05 lux 1/3" CCD camera and single-channel FCC-approved Part 15 Low Power 700 ft. 2.4 GHz wireless video transmitter/3dB receiver. <ul style="list-style-type: none"> Fully functional AM/FM clock radio Color, 380 TVL, 0.5 lux 1/4" CCD camera single-channel FCC-approved Part 15 Low Power 700 ft. 2.4 GHz wireless video transmitter/3dB receiver. <p>Different Distance Configurations Available.</p>	<p>B & W \$350.00</p> <p>Color \$450.00</p>
Alarm Clock Camera1 - Wireless		<p>Camera Specifications:</p> <ul style="list-style-type: none"> Fully functional AM/FM clock radio with B/W, 420 TVL, .05 lux 1/3" CCD camera and single-channel FCC-approved Part 15 Low Power 700 ft. 2.4 GHz wireless video transmitter/3dB receiver. Fully functional AM/FM clock radio with Color, 380 TVL, 0.5 lux 1/4" CCD camera and single-channel FCC-approved Part 15 Low Power 700 ft. 2.4 GHz wireless video transmitter/3dB receiver. <p>Different Distance Configurations Available.</p>	\$350.00
Alarm Clock/Lamp Wireless		<p>Camera Specifications:</p> <ul style="list-style-type: none"> 92 degree field of view 3.6mm Lens 1/3 DSP Color CCD image Sensor 1/4 DSP B/W 380 lines of resolutions color, 420 lines B/W 0.5 LUX color, .05 B/W DC 12V power NTSC Audio is not available <p>Transmitter / Receiver Specifications:</p> <ul style="list-style-type: none"> 4-channel operations (camera) 8 channel scroll capable (receiver) 300 - 700 foot line of sight (LOS) approximate range (LOS is dependent upon, obstructions and interference from other wireless devices) 	\$375.00
Clock 1 Wireless		<p>Camera Specifications:</p> <ul style="list-style-type: none"> 92 degree field of view 3.6mm Lens 1/3 DSP Color CCD image Sensor 1/4 DSP B/W 380 lines of resolutions color, 420 lines B/W 0.5 LUX color, .05 B/W DC 12V power NTSC Audio is not available 	\$375.00

PRODUCT NAME	PRODUCT IMAGE	PRODUCT SPECS	PRICE
		<ul style="list-style-type: none"> • Transmitter / Receiver Specifications: • 4-channel operations (camera) • 8 channel scroll capable (receiver) • 300 – 700 foot line of sight (LOS) approximate range • (LOS is dependent upon, obstructions and interference from other wireless devices) 	
Clock 2 Wireless		<p>Camera Specifications:</p> <ul style="list-style-type: none"> • 92 degree field of view • 3.6mm Lens • 1/3 DSP Color CCD image Sensor ¼ DSP B/W • 380 lines of resolutions color, 420 lines B/W • 0.5 LUX color, .05 B/W • DC 12V power • NTSC • Audio is not available <p>Transmitter / Receiver Specifications:</p> <ul style="list-style-type: none"> • 4-channel operations (camera) • 8 channel scroll capable (receiver) • 300 – 700 foot line of sight (LOS) approximate range • (LOS is dependent upon, obstructions and interference from other wireless devices) 	\$375.00
Pen Wireless		<p>Camera Specifications:</p>	\$260.00
Pencil Sharpener Wireless		<p>Camera Specifications:</p> <ul style="list-style-type: none"> • 92 degree field of view • 3.6mm Lens • 1/3 DSP Color CCD image Sensor ¼ DSP B/W • 380 lines of resolutions color, 420 lines B/W • 0.5 LUX color, .05 B/W • DC 12V power • NTSC • Audio is not available <p>Transmitter / Receiver Specifications:</p> <ul style="list-style-type: none"> • 4-channel operations (camera) • 8 channel scroll capable (receiver) • 300 – 700 foot line of sight (LOS) approximate range • (LOS is dependent upon, obstructions and interference from other wireless devices) 	\$325.00

PRODUCT NAME	PRODUCT IMAGE	PRODUCT SPECS	PRICE
Picture Frame 1 Wireless		<p>Camera Specifications:</p> <ul style="list-style-type: none"> • 92 degree field of view • 3.6mm Lens • 1/3 DSP Color CCD image Sensor 1/4 DSP B/W • 380 lines of resolutions color, 420 lines B/W • 0.5 LUX color, .05 B/W • DC 12V power • NTSC • Audio is not available <p>Transmitter / Receiver Specifications:</p> <ul style="list-style-type: none"> • 4-channel operations (camera) • 8 channel scroll capable (receiver) • 300 – 700 foot line of sight (LOS) approximate range • (LOS is dependent upon, obstructions and interference from other wireless devices) 	\$375.00
PIR-NF-Video Only		<p>Camera Specifications:</p> <ul style="list-style-type: none"> • 92 degree field of view • 3.6mm Lens • 1/3 DSP Color CCD image Sensor 1/4 DSP B/W • 380 lines of resolutions color, 420 lines B/W • 0.5 LUX color, .05 B/W • DC 12V power • NTSC • Audio is not available <p>Transmitter / Receiver Specifications:</p> <ul style="list-style-type: none"> • 4- channel operations (camera) • 8 channel scroll capable (receiver) • 300 – 700 foot line of sight (LOS) approximate range • (LOS is dependent upon, obstructions and interference from other wireless devices) • Size 4 3/4" x 2 3/4" x 1 7/8" 	\$275.00
Radio Camera -1 Wireless		<p>Camera Specifications:</p> <ul style="list-style-type: none"> • Fully functional AM/FM radio • B/W, 420 TVL, .05 lux • 1/3" CCD camera and single-channel • FCC-approved Part 15 Low Power 700 ft. 2.4 GHz wireless video transmitter/3dB receiver. <ul style="list-style-type: none"> • Fully functional AM/FM radio • Color, 380 TVL, 0.5 lux • 1/4" CCD camera and single-channel • FCC-approved Part 15 Low Power 700 ft. 2.4 GHz wireless video transmitter/3dB receiver. <p>Different Distance Configurations Available.</p>	<p>B & W \$375.00</p> <p>Color \$475.00</p>

PRODUCT NAME	PRODUCT IMAGE	PRODUCT SPECS	PRICE
Radio Camera - 2 Stereo - Wireless		<p>Camera Specifications:</p> <ul style="list-style-type: none"> • 92 degree field of view • 3.6mm Lens • 1/3 DSP Color CCD image Sensor 1/4 DSP B/W • 380 lines of resolutions color 420 lines B/W • 0.5 LUX Color .05 B/W • DC 12V power • NTSC • Audio is not available <p>Transmitter / Receiver Specifications: 4-channel operations (camera) 8 channel scroll capable (receiver) 300 – 700 foot line of sight (LOS) approximate range (LOS is dependent upon, obstructions and interference from other wireless devices)</p> <p>Includes Hidden Video camera systems Power supply RCA Cable Instructions Size 11" x 17" x 7 1/4"</p>	\$450.00
Screw Camera		<p>Camera Specifications:</p> <ul style="list-style-type: none"> • 92 degree field of view • 3.6mm Lens • 1/3 DSP Color CCD image Sensor 1/4 DSP B/W • 380 lines of resolutions color, 420 lines B/W • 0.5 LUX Color, .05 B/W • DC 12V power • NTSC 	\$195.00
Smoke Detector-HW 1		<p>Camera Specifications:</p> <ul style="list-style-type: none"> • 92 degree field of view • 3.6mm Lens • 1/3 DSP Color CCD image Sensor 1/4 DSP B/W • 380 lines of resolutions color, 420 lines B/W • 0.5 LUX Color, .05 B/W • DC 12V power • NTSC • Power supply • RCA Cable • Instructions 	\$200.00

PRODUCT NAME	PRODUCT IMAGE	PRODUCT SPECS	PRICE
Smoke Detector-HW 2		Camera Specifications: <ul style="list-style-type: none"> • SONY CCD 470TVL 0.1Lux • Output & 3.7mm Pinhole Lens • DC12V / 150mA Video-Audio	\$195.00
Smoke Detector-HW 3 Multi Video Security Camera Covert Smoke Detector	Add up to 3 additional cameras for a full 360° view  20° swivel cam adjustment for optimal view	Camera Specifications: <ul style="list-style-type: none"> • Add up to 3 additional cameras for a full 360° view • 380 lines of resolution, .05 lux • 9-15V DC, 110mA, Sony Chipset • Upgradeable to 4 total cameras • 20° swivel cam adjustment for optimal view • Smoke detector is non-functional. Includes red LED on housing to simulate an operational detector 	\$145.00 1 camera Additional Cameras \$90.00 Each
Fire Sprinkler 1		Camera Specifications: <ul style="list-style-type: none"> • CCD pixels NTSC 537 x 505 • Minimum illumination 0.5 LUX • 420 lines TV resolution • Pinhole 4.3mm lens • Video out put composite 1.0V p-p at 75 ohm • Power supply DC 12V Includes Sprinkler camera AC adapter Manual	\$195.00
Fire Sprinkler 2		Camera Specifications: <ul style="list-style-type: none"> • Image Sensor: 1/4" SONY CCD • Picture elements : EIA/NTSC: 512 H x 492 V - CCIR/PAL: 512 H x 582 V • Horizontal resolution: 420 TVL • Minimum Illumination: 0.1 Lux • Horizontal Sync. frequency: EIA//NTSC: 15.734 KHZ - CCIR/PAL: 15.625 KHZ • Vertical frequency : EIA//NTSC: 60 HZ - CCIR/PAL: 50 HZ • Clock frequency: EIA//NTSC: 19.0699 MHZ - CCIR/PAL: 18.9375 MHZ • Lens: Pinhole Lens 3.7mm • Video output: 1Vp-p , 75 Ohms • Gamma: 0.45 • Power supply : DC12V • Power Consumption: 150 mA • Storage Temperature : -30°C ~ 60°C • Operation Temperature : -10°C ~ 45°C 	\$175.00

PRODUCT NAME	PRODUCT IMAGE	PRODUCT SPECS	PRICE
Thermostat		Camera Specifications: <ul style="list-style-type: none"> Fully functional thermostat works with most air conditioners and heaters Standard residential/business styling works in numerous environments Camera is configured to look forward from behind temperature gauge 	B & W 3.6mm Lens \$260.00 Wide Angle 120 degree Lens \$345.00 Day / Night 3.6mm Lens \$395.00
Sports Bag 1		Camera Specifications: <ul style="list-style-type: none"> 92 degree field of view 3.6mm Lens 1/3 DSP Color CCD image Sensor 1/4 DSP B/W 380 lines of resolutions color 420 lines B/W 0.5 LUX Color .05 B/W DC 12V power NTSC Audio is not available Includes Hidden Video camera systems Power supply/12 Volt Battery Pack RCA Cable Instructions Hardwire and Wireless Configurations Available	\$425.00
Bag Camera 2 Hardwire		Camera Specifications: <ul style="list-style-type: none"> 92 degree field of view 3.6mm Lens 1/3 DSP Color CCD image Sensor 1/4 DSP B/W 380 lines of resolutions color 420 lines B/W 0.5 LUX Color .05 B/W DC 12V power NTSC Audio is not available 	\$350.00

PRODUCT NAME	PRODUCT IMAGE	PRODUCT SPECS	PRICE
Button Camera 1		<p>Camera Specifications:</p> <ul style="list-style-type: none"> • 92 degree field of view • 3.6mm Lens • 1/3 DSP Color CCD image Sensor 1/4 DSP B/W • 380 lines of resolutions color, 420 lines B/W • 0.5 LUX Color, .05 B/W • DC 12V power • NTSC • Power supply • RCA Cable • Instructions <p>Video/Audio</p>	\$185.00
Tie Camera 1		<p>Camera Specifications:</p> <ul style="list-style-type: none"> • 92 degree field of view • 3.6mm Lens • 1/3 DSP Color CCD image Sensor 1/4 DSP B/W • 380 lines of resolutions color, 420 lines B/W • 0.5 LUX Color, .05 B/W • DC 12V power • NTSC • Power supply • RCA Cable • Instructions 	\$195.00
VHS Case Camera Wireless		<p>Camera Specifications:</p> <ul style="list-style-type: none"> • 92 degree field of view • 3.6mm Lens • 1/3 DSP Color CCD image Sensor 1/4 DSP B/W • 380 lines of resolutions color, 420 lines B/W • 0.5 LUX Color, .05 B/W • DC 12V power • NTSC • Power supply • RCA Cable • Instructions 	\$325.00
Clock Camera – 1 Wireless		<p>Camera Specifications:</p> <ul style="list-style-type: none"> • 420 Lines of Resolution • 0.05 Lux • 4 Channel 1000' Wireless TX • Includes 12-Volt DC Power Adapters • Fully-Functional Residential Wall Clock 	\$425.00

PRODUCT NAME	PRODUCT IMAGE	PRODUCT SPECS	PRICE
Sun Glasses 1		<p>Camera Specifications:</p> <ul style="list-style-type: none"> • 1/4 color CCD image sensor NTSC • 350 resolution TV lines • 0.5 LUX • 3.7 mm Built in lens • DC 12Volt • Clear lenses Item available <p>Includes Sun Glasses AV Cable Battery pack (uses 8 AA batteries not included) (6 to 8 hours use) Size 6" x 2" x 2 3/4"</p>	\$575.00
Copper SD-DVR		<p>Specifications:</p> <ul style="list-style-type: none"> • Auto detection of NTSC or PAL • Quality level, High, Medium or low • Manual, Motion detection and scheduled recording • Frame rate max. 704x480 @ 24fps • AV IN/OUT • Video MPEG4 ASF • Supports 1 channel video/audio recorded directly to the SD card with FAT16/32 • Time and date stamp overlay • Storage secure digital card (not included) • Adjustable sensitivity of motion detection • Power 2 AA batteries (not included) approximate record time 3 hours • AC adapter 5V DC • 1GB card record time is approximately 5 hours in standard record mode • Key lock function <p>Includes Motion activated security recorder 2 audio/video cables AC power adapter Manual Quick installation guide Size 2 1/2" x 3 1/2" x 1"</p>	\$295.00
MVR-SD100		<p>Specifications:</p> <ul style="list-style-type: none"> • Rechargeable Lithium-ion battery for up to 2 hours record / playback • AV in -AV out • Full - stop, motion, alarm and overwrite recording modes • Auto file save with sudden power loss • CMOS 1.3M pixels 60 degree FOV • Date and time stamp • NTSC / PAL 	\$625.00

PRODUCT NAME	PRODUCT IMAGE	PRODUCT SPECS	PRICE
		<ul style="list-style-type: none">• 320 x 240 / 640 x 480 resolution• 128MB internal memory• SD memory card slot for additional memory supports up to 1GB card <p>Includes: Motion activated DVR External Camera Rechargeable Battery AV cables Power supply/charger Carrying case Remote Switch Size 3 1/2" x 1 3/4" x 1"</p>	